

# PRO MEDIA 2.1 BT



## LEGENDARY SOUND FROM A LEGENDARY PRODUCT, NOW WITH BLUETOOTH

The Klipsch ProMedia 2.1BT is the next generation of the legendary Klipsch ProMedia 2.1, which singlehandedly raised the bar on what is defined as exceptional sound from CDs, MP3s or other compressed file formats, and streaming radio. Upgraded now with Bluetooth connectivity, the new ProMedia 2.1BT raises the bar on performance and connectivity. Wirelessly stream audio from your laptop, smartphone or tablet and enjoy wireless sound in your den, office, living room or wherever you choose to set up the system.

#### **EXCLUSIVE HORN-LOADED TECHNOLOGY**

Klipsch MicroTractrix® horns make a major contribution to the ProMedia 2.1 BT's amazing proficiency. Their highly efficient design reproduces more sound from every watt of power, controlling the dispersion of that sound and sending it straight to your ears for clarity and lifelike impact no other system can duplicate.

#### **CLEAN BASS OUTPUT AT ALL VOLUME LEVELS**

The two-way satellites' 3" midbass drivers blend perfectly with the Promedia 2.1 BT's solid, 6.5" side-firing, ported subwoofer for full bandwidth bass response you can actually feel. With a separate subwoofer volume control, you can adjust for the best bass for what you're listening to.

### PERFORMANCE THAT CREATES FLEXIBILITY

With its plug and play setup and convenient 3.5mm input, the Promedia 2.1 BT can double from anything from a TV sound enhancer to a 2.1 Home Theater system. It's 200 watts of dynamic system power can fill even a larger room with sound. The headphone jack allows for private listening when desired.

SPECIFICATIONS	
System Power	Total System Power: 100 watts continuous/200 watts peak @ <0.2% THD 260 watts short-term peak power
	Satellites: 18 watts/channel continuous @ <0.2% THD, 1kHz 26 watts/channel short-term power @ <5% THD, 1kHz
	Subwoofer: 65 watts continuous @ <0.2% THD, 50 Hz 80 watts short-term power @ <5% THD, 50Hz
Built From	2016
Frequency Response	35Hz ~ 22kHz
Satellite Crossover Frequency	3.5kHz
Enclosure Material	Satellites: ABS Subwoofer: MDF
Enclosure Type	Satellites: Sealed Subwoofer: Bass Reflex
High Frequency Horn	90° x 40° MicroTractrix®
Inputs	3.5mm miniplug Bluetooth 2.0
Typical Maximum Output	110dB SPL (in-room)
Outputs	3.5mm miniplug Headphone
Dimensions	Satellite: 8.5" (21.59cm) x 4.2" (10.67cm) x 5.67" (14.4cm) Subwoofer: 9.5" 24.13cm) x 9.8" (24.9cm) x 10.2" (25.9cm)
Finish	Black
Subwoofer	One, side-firing 6.5" (16.51cm) long-throw fiber composite cone
Tweeter	19mm PEI dome
Voltage	110/120 VAC
Weight	Satellite: 2.1lbs (0.95kg) Subwoofer: 11 lbs (5kg)

