

PRO-1200SW

12" IN-WALL SUBWOOFER



HIDDEN HIGH PERFORMANCE

A true subwoofer for both music and movies, the PRO-1200SW provides clean, dynamic, powerful low frequencies while its behind-the-drywall design keeps it hidden from view. Simple, easy-to-install design allows for direct, secure installation into a new construction standard 16" OC stud bay using included wood screws for retrofit or new construction. The drywall can be installed over the front face of the cabinet, with a 14"x14" cutout exposing the driver.

HIGH PERFORMANCE ACOUSTICS

12" long-throw Cerametallic™ woofer with reverse rolled surround provides dynamic, balanced, powerful low frequencies - all within a traditional stud bay. Maximize the output and acoustic performance using the KDA Series DSP amplifiers, which include presets for optimized EQ and limiter settings custom designed by Klipsch engineers specifically for the PRO-1200SW.

MDF ENCLOSURE

The durable, robust MDF enclosure, provides accurate, powerful low frequencies while helping to isolate sound from neighboring rooms.

MAGNETIC, PAINTABLE GRILLE

Magnetic, bezel-free, paintable grille blends seamlessly into even the most luxurious of living spaces and home theaters.

SPECIFICATIONS

FREQUENCY RANGE*	21Hz - 100Hz +/- 3dB
SYSTEM TYPE	Sealed Box
WOOFER	12" (25.4cm) Long-Throw Cerametallic™
MAXIMUM OUTPUT*	112dB @ 70Hz
POWER HANDLING	250W RMS / 600W Peak
IMPEDANCE	8 Ohm
ENCLOSURE MATERIAL	MDF
FINISH	Black Polymer Veneer with White, Paintable Grille
PRODUCT DIMENSIONS	60.71" H x 15.67" W x 3.94" D (1542mm x 398mm x 100mm)
MOUNTING DEPTH	3.4" (88mm)
CUTOUT DIMENSIONS	14.1" x 14.1" (359mm x 359mm)
PRODUCT WEIGHT	35.5 lbs (16.1 kg)
BUILT FROM	2017

* With Klipsch KDA Amplifier DSP Preset